Face Recognition &Temperature Detection



FRT-B8x

Facial Recognition & Temperature Detection & Mask Detection 3-in-1 System



Key features

- Non-contact automatic Body Temperature Detection
- Support No Mask Detection
- Support Voice Alarm (For Abnormal temperature,
- No Mask)
- Unique Facial Recognition algorithm.
- Facial Recognition time < 1 second
- Face Database ≥30 000 faces
- 8-inch IPS HD display
- Used to prohibit epidemic of COVID-19 by detecting human temperature and require mask wearing.

Specifications

| Temperature & Mask Detection | |
|---|--|
| Temperature Range&Accuracy | Range: 30-45(°C) |
| | Accuracy:±0.3°C/Indoor |
| Detection Distance | 0.5-1m |
| Temperature Detection | Support |
| Mask Detection | Support |
| Wask Botodion | Support (For Abnormal Temperature and |
| Voice Alarm | No Mask) |
| Facial Recognition | . To masky |
| Recognition Accuracy | ≥99.7% |
| Recognition time | <1second |
| Face Database | ≥30 000 faces |
| Recognition Distance&Height | Distance: 0.5~2 m Height:1.2~2.2m, |
| | Adjustable |
| Recognized Face Angle | ≥30° |
| Lens Angle | 2.8mm,H 117.8°, V 64.1°, D: 141.9° |
| Black & White List | Support |
| Interface | |
| Ethernet | 10M/100M Ethernet, RJ45 Port |
| Wiegand Interface | 1 pcs for output |
| RS232 & RS485 | Support |
| Alarm Output | Cupport |
| Micro-SD Card | Support |
| | Support, upto 128GB |
| Audio Input&Output | Support, upto 128GB |
| Audio Input&Output USB Interface | |
| | Support, upto 128GB Support, with Built-in Speaker |
| USB Interface | Support, upto 128GB Support, with Built-in Speaker |
| USB Interface General | Support, upto 128GB Support, with Built-in Speaker 1PCS |
| USB Interface General Working Temperature | Support, upto 128GB Support, with Built-in Speaker 1PCS -30°C-+60°C |
| USB Interface General Working Temperature Working Humidity | Support, upto 128GB Support, with Built-in Speaker 1PCS -30°C-+60°C RH 5~90% |
| USB Interface General Working Temperature Working Humidity Power Supply | Support, upto 128GB Support, with Built-in Speaker 1PCS -30°C - +60°C RH 5~90% DC12V 3.33A |
| USB Interface General Working Temperature Working Humidity Power Supply Power Consumption | Support, upto 128GB Support, with Built-in Speaker 1PCS -30°C - +60°C RH 5~90% DC12V 3.33A <20W |
| USB Interface General Working Temperature Working Humidity Power Supply Power Consumption Dimensions | Support, upto 128GB Support, with Built-in Speaker 1PCS -30°C - +60°C RH 5~90% DC12V 3.33A <20W 273mm*144mm*25mm |
| USB Interface General Working Temperature Working Humidity Power Supply Power Consumption Dimensions Diameter for Install on Gate | Support, upto 128GB Support, with Built-in Speaker 1PCS -30°C - +60°C RH 5~90% DC12V 3.33A ≤20W 273mm*144mm*25mm 30mm |



